



TUV T8 Xtra

TUV 36W Xtra 1SL

TUV T8 Xtra lamps are double ended UVC (germicidal) lamps used in professional water and air disinfection units. Thanks to the unique X-technology TUV T8 Xtra lamps even double the life of conventional types. This extra long and reliable lifetime is even up to 36,000 hours when the lamps are operated on HF gear. As a result these lamps need to be replaced less often, significantly reducing cost and disruption. Thanks to the reliable lifetime, maintenance can be planned in advance

Product data

• General Characteristics

System Description	-
Cap-Base	G13
Bulb	T26
Main Application	Disinfection
Useful Life	18000 hr

• Electrical Characteristics

Lamp Wattage	36 W
Lamp Wattage Technical	36 W
Lamp Voltage	103 V
Lamp Current	0.44 A

• Environmental Characteristics

Mercury (Hg) Content	3.0 mg
----------------------	--------

• Light Technical Characteristics

Color Designation (text)	-
--------------------------	---

• UV-related Characteristics

UV-C Radiation	15.0 W
----------------	--------


• Product Dimensions

Base Face to Base Face A	1199.4 (max) mm
Insertion Length B	1204.1 (min), 1206.5 (max) mm
Overall Length C	1213.6 (max) mm
Diameter D	28 (max) mm


• Product Data

Order code	928039904008
Full product code	928039904008
Full product name	TUV 36W Xtra 1SL
Order product name	TUV 36W Xtra 1SL/6
Pieces per pack	1
Packing configuration	6
Packs per outerbox	6
Bar code on pack - EAN1	8711500265098
Bar code on outerbox - EAN3	8711500265104
Logistic code(s) - 12NC	928039904008
Net weight per piece	173.000 gr



Dimensional drawing



Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TUV TL-D 36W Xtra	1199.4	1204.1	1206.5	1213.6	28



Photometric data



© 2011 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2011, July 25
data subject to change